





CLIMCOVER Lamella Mat

Aluminium faced glass wool lamella mat for thermal insulation of metal ducts and HVAC equipment

ISOVER CLIMCOVER Lamella Mat provides thermal and acoustic insulation for circular metal ductwork, tanks and large diameter pipes. The high mechanical resistance of CLIMCOVER Lamella Mat makes it ideal for use at all levels, inside or outside a building (with appropriate covering).

The lamella mat is faced on one side with a reinforced pure aluminium foil that acts as vapour barrier. The reinforcement mesh increases the resistance to tearing and punching of the aluminium. Mat is resistant to mechical load but still flexible and can be easily bend over different shapes and parts of HVAC systems The facing can be used as shiplap that permits the easy assembly and connexion between wrap insulation pieces. The roll is easy to cut with standard tools iex. knife CLIMCOVER Lamella Mats are manufactured from inorganic chemically biosoluble materials and do not include anything that would have effect on corrosion and shall not facilitate microbial growth.



MECHANICAL RESISTANCE

Improved mechanical strenght to improve the aesthetics and carry the weight of the cladding



THERMAL INSULATION

Avoid heat losses and prevent condensation



LIGHTWEIGHT

Lightweigth rolls are easy to work with in all conditions



FAST INSTALLATION

The highly flexible product is easy to bend over different shapes and parts, and easy to cut with standard tools



CLIMCOVER Lamella Mat



CHARACTERISTIC	SYMBOL	UNIT	QUANTITIES AND DECLARED VALUES					STANDARD
Thermal Conductivity	Т	[ºC]	10	50	100	200	250	EN 12667
	λ	[W/(m·K)]	0.038	0.045	0.060	0.102	0.130	
Maximum service temperature	-	[ºC]	<250°C (for the facing 80°C)					EN 14303

CHARACTERISTIC	SYMBOL	UNIT	QUANTITIES AND DECLARED VALUES	STANDARD
Fire behaviour	-	-	Non combustible, Euroclass A2-s1, d0	EN 13501-1
Water behaviour	SD	m	≥100	EN 12086
Application field	-	-	ISOVER CLIMCOVER Lamella Mat provides mechanically strong thermal insulation for HVAC duct systems and equipment. Alufacing provides efficient watervapour barrier when intact and seems carefully taped.	EN 14303
CE marking	-	-	MW-EN14303-T3-ST 250-WS1-MV2	EN14303
Environmental sustaina- bility	-	-	ISOVER CLIMCOVER Lamella Mat is manufactured from up to 86% recycled glass that would otherwise go to landfill. This makes ISOVER one of the most environmentally sustainable insulation products on the market today.	-
Quality management	-	-	ISOVER is certified according to EN ISO 9001 and EN ISO 14001	EN ISO 9001 EN ISO 14001
Delivery form	-	-	Standard dimensions (check product details and availability from your local ISOVER supplier)	-









www.isover-technical-insulation.com

The technical information corresponds to our present state of knowledge and experience at the date of printing (see imprint). But no legal guarantee can be given, unless it has been explicitly agreed. The state of experience and knowledge is developing continuously. Please see to it that you always use the latest edition of this information. The described product applications do not take special circumstances in consideration. Please verify whether our products are appropriate for the concrete application. For further information please contact our Isover sales offices. We deliver only according to our terms of trade and terms of delivery.

SAINT-GOBAIN ISOVER · Tour Saint-Gobain 12 place de l'Iris 92096 La Défense cedex - France

